



Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: B14 SAPPHIRE BLUE NON CHROMATE S/B PRIMER
Product code: 2191441
Print Date: 10/Sep/2013
Revision Date: 10/Sep/2013
Recommended use: A coating or solution for industrial use

Company Identification:

Manufacturer, importer, supplier: The Valspar (Australia) Corporation Pty. Ltd.
203 Power Street
Glendenning, N.S.W. 2761
+61 (02) 9839 1111

Australia Emergency telephone number: 1800 033 111 and +64 4473 4607

Australia Poisons Information Centre 24 hours: 131-126, New Zealand: 0800 764766

2. HAZARDS IDENTIFICATION

Classified as hazardous according to criteria of NOHSC.
Classified as DANGEROUS according to the Australian Dangerous Goods Code.

Indication of danger:

F - Highly flammable
Xn - Harmful

Risk Phrases

R11 - Highly flammable.
R38 - Irritating to skin.
R20/21 - Harmful by inhalation and in contact with skin.
R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2. HAZARDS IDENTIFICATION

S-phrase(s)

S 9 - Keep container in a well-ventilated place.
S16 - Keep away from sources of ignition - No smoking.
S33 - Take precautionary measures against static discharges.
S23 - Do not breathe gas/fumes/vapour/spray.
S51 - Use only in well-ventilated areas.

S36/37 - Wear suitable protective clothing and gloves.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name
XYLENE 1330-20-7	50-70	Xylenes (o-, m-, p- isomers)
ETHYLBENZENE 100-41-4	10-30	Ethyl benzene
TRIZINC BIS(ORTHOPHOSPHATE) 7779-90-0	1-5	Phosphoric acid, zinc salt (2:3)
ZINC OXIDE 1314-13-2	0.2-0.5	ZINC OXIDE

If this section is blank, there are no hazardous components per NOHSC guidelines.

4. FIRST AID MEASURES

General

If symptoms persist, call a physician. Never give anything by mouth to an unconscious person.

Skin:

Take off all contaminated clothing immediately. Wash off immediately with soap and plenty of water. Do NOT use solvents or thinners.

Eyes:

Remove contact lenses. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Keep eye wide open while rinsing.

Inhalation:

Move to fresh air. If victim is unconscious but breathing: Victim to lie down in the recovery position, cover and keep him warm. If not breathing, give artificial respiration. Obtain medical attention.

Ingestion:

Keep at rest. If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting.

5. FIRE FIGHTING MEASURES

Hazchem Code: 3YE
Flash point: 1
Lower explosive limit: 1
Upper explosive limit: 7.7
Autoignition temperature: not determined

The following actions are recommended

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire will produce dense black smoke containing hazardous combustion products (see heading 10).
Wear self contained breathing apparatus for fire fighting if necessary.
Cool containers / tanks with water spray.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Carbon dioxide (CO₂)

Dry powder

Extinguishing media which must not be used for safety reasons

High volume water jet

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Exclude non essential personnel. Remove all sources of ignition. Ensure adequate ventilation. Do not breathe vapours/dust.

Environmental precautions:

Local authorities should be advised if significant spillages cannot be contained.

Methods for cleaning up:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Clean with detergents. Avoid solvents.

7. HANDLING AND STORAGE

Handling:

Operators should wear anti-static footwear and clothing. Use only non-sparking tools. Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards. Vapours are heavier than air and may spread along floors. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Provide adequate ventilation. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Keep container tightly closed. Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with skin and eyes. Do not breathe vapours or spray mist. When using, do not eat, drink or smoke. Do not use pressure to empty drums. Store in original container.

Storage:

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Take notice of the directions of use on the label. Keep in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep away from direct sunlight. Store in a place accessible by authorized persons only. Do not smoke.

Storage temperature:

10 - 30 C

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits:

Australia:

Ingredient Name CAS-No.	Australia OELs - TWA	Australia OELs - STEL	Australia OELs - Skin Designation
XYLENE 1330-20-7	350 mg/m ³ TWA 80 ppm TWA	150 ppm STEL 655 mg/m ³ STEL	
ETHYLBENZENE 100-41-4	100 ppm TWA 434 mg/m ³ TWA	125 ppm STEL 543 mg/m ³ STEL	
ZINC OXIDE 1314-13-2	10 mg/m ³ TWA dust 5 mg/m ³ TWA fume	10 mg/m ³ STEL dust and fume	

Engineering measures:

During curing, decomposition products may be formed, which should be extracted safely from the work area. Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Basic Personal Protection**Respiration**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection:

Wear suitable gloves and eye/face protection. Use protective skin cream before handling the product.

Skin:

Wear as appropriate: Flame retardant antistatic protective clothing Wear shoes with conductive soles.

Eyes:

Wear as appropriate: Safety glasses with side-shields Goggles

Hygiene measures:

Do not use solvents or thinners to clean skin. When using, do not eat, drink or smoke. Wash hands before breaks and at the end of workday. It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	liquid
Vapor pressure:	90.2255639 mmHg @77° F (25° C)
Vapor density (air = 1.0):	3.7
Solubility in water:	not determined
Flash point:	1°C
Boiling point/range	136°C
Specific Gravity	1.01
Evaporation rate (butyl acetate = 1.0):	0.81

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to avoid:	Stable under recommended storage conditions.
Materials to avoid:	Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
Hazardous Polymerization:	None anticipated.
Hazardous decomposition products:	Hazardous decomposition products may be produced when the recommended processing temperatures or times are exceeded. Carbon monoxide Carbon dioxide (CO ₂) Smoke nitrogen oxides (NO _x)

11. TOXICOLOGICAL INFORMATION**Potential Acute Health Effects:****Eye contact:**

May cause eye irritation.

Skin contact:

Causes skin irritation.

Harmful in contact with skin.

Ingestion:

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Inhalation:

May cause irritation of respiratory tract.

Harmful by inhalation.

11. TOXICOLOGICAL INFORMATION

Target Organ and Other Health Effects:

Causes headache, drowsiness or other effects to the central nervous system.

Liver injury may occur.

Kidney injury may occur.

If this section is blank, no information is available.

12. ECOLOGICAL INFORMATION

Air Pollutant

Local pollution requirements may apply to the use of this product. Do not let product enter drains. Do not contaminate surface water.

13. DISPOSAL CONSIDERATIONS

Waste disposal methods:

Do not let product enter drains. Do not contaminate ponds, waterways or ditches with chemical or used container. Where possible recycling is preferred to disposal or incineration. Dispose of as special waste in compliance with local and national regulations.

14. TRANSPORTATION INFORMATION

Australia ADG:

Proper shipping name: PAINT
UN/ID No: UN1263
Hazard class: 3
Packing group: II
Hazchem Code: 3YE

IMDG:

Proper shipping name: PAINT
UN/ID No: UN1263
Hazard class: 3
Packing group: II

IATA:

Proper shipping name: Paint
UN/ID No: UN1263
Hazard class: 3
Packing group: II

15. REGULATORY INFORMATION

AICS Australian Inventory:

This product/preparation is in compliance with the Australian Inventory of Chemical Substances (AICS) list.

Label Information:

contains

XYLENE

Indication of danger:

F - Highly flammable Xn - Harmful

**Risk Phrases**

R11 - Highly flammable.

R38 - Irritating to skin.

R20/21 - Harmful by inhalation and in contact with skin.

R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrase(s)

S 9 - Keep container in a well-ventilated place.

S16 - Keep away from sources of ignition - No smoking.

S33 - Take precautionary measures against static discharges.

S23 - Do not breathe gas/fumes/vapour/spray.

S51 - Use only in well-ventilated areas.

S36/37 - Wear suitable protective clothing and gloves.

16. OTHER INFORMATION

Print Date: 10/Sep/2013

Revision Date: 10/Sep/2013

Abbreviations:

NOHSC - National Occupational Health and Safety Commission, AICS - Australia Inventory of Chemical Substances, EC - European Community, ADR - Australia Code for the Transportation of Dangerous Goods by Road and Rail, IATA - International Air Transport Association, IMDG - International Maritime Dangerous Goods, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, WT - Weight, mg/m³ - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.